

## T5000 Series BEVERAGE / BEER PUMPS GAS (C02)/AIR DRIVEN

Part Number 24000022



Designed for dispensing Bag-in-Box syrups, juice concentrate (without pulp or particulates), teas, wines, and liquor

Supplies the following from remote location:

Four (4) 3.0 oz. (89 ml) valves1


or

Two (2) 4.5 oz. (133 ml) valves2

1Each valve dispenses syrup at 0.50 oz./sec.

2Each valve dispenses syrup at 0.75 oz./sec

- Service life of 40,000 gallons (150,000 L)
- Compact design with quick disconnect fittings for simple, quick installation
- Shuts off automatically when bag is empty and restarts when a full bag is connected
- High altitude auto shut-off also available
- Fully automatic, operates only when beverage is being dispensed
- 1/4" (6.35 mm) barbed, CO2 exhaust port connection for venting away from confined areas
- Maintains constant pressure at the dispensing valve
- High suction capability empties syrup down to a minimum residual
- Recyclable materials



Dimensions	Width: 156.8mm, Depth: 61.5mm, Height: 131.3mm
Weight	0.54 kg
Temperature Limits	34° - 120° F (1.1° - 49° C)
Pump Design	Positive Displacement, Double Diaphragm
Power Source	CO2 Gas, Nitrogen or Compressed Dry Filtered Air
Displacement	2.5 oz. per cycle
Self-Priming	Up to 10 ft. (3.05 m)
Operating Pressure	20 PSI (1.4 bar) min. / 80 psi (5.5 bar) max.
Liquid Inlet Pressure	10 PSI (0.7 bar) max.
Flow Rate	4.0 oz. (118.3 ml)/sec Open Flow
Approvals	CE, SK, NSF Standard 18



## Warranty