

CO2 Mk9 Sensor Add-on KIT (2117)

with amber Horn/Strobe, for LogiCO2 Safety System



FUNCTION

The Carbon Dioxide (CO2) Safety System is designed to measure CO2 concentration in a confined space environment. It provides an alarm in the event that a CO2 level considered unhealthy/dangerous in accordance with existing safety codes, in the area being monitored.

The CO2 Sensor KIT is a precision instrument comprising one Sensor Unit and one Horn/Strobe. The CO2 Sensor KIT is an add-on sensor for an existing Safety System and it is pre-set with the address: ID2. The CO2 Sensor KIT receives it's power from the existing Safety System. The Safety Systems Central Unit must be set to receive measuring values from two Sensors. See section "DIP-switch settings, Number of connected sensors" in the CO2 Safety System's User's Manual.

TECHNICAL DATA

Power supply:	12-24V DC
Power consumption:	155 mA peak
Communication:	RS485 Modbus
Automatic calibration:	Several times a year

For further data see separate data sheets for the specific components.

When installed properly, the CO2 Safety System will continuously monitor the CO2 concentration and temperature wherever a sensor unit is located. A green light emitting diode (LED) on the central unit indicates normal safe conditions. If ambient conditions at the CO2 Sensor reach a CO2 concentration level of 1.5% (preset low alarm), the central unit will emit an intermittent audible tone and the « low alarm » red LED will blink. A remote Horn/Strobe will flash. This will also happen if the TWA for 8 hours also surpasses 5000 ppm. The difference can be acknowledged on the display. If ambient conditions at the CO2 Sensor reach a CO2 concentration level of 3.0% (preset high alarm), the central unit will emit a constant audible tone and the « high alarm » red LED lights. A remote Horn/Strobe will flash and sound.

ORDERING EXAMPLE

Description	Item code
CO2 Mk9 Sensor kit	2117

CO2 Mk9 Sensor kit consists of:

- CO2 Sensor Mk9
- Cable red 10m
- Cable blue 5m
- Horn/Strobe LED amber with 1m cable
- RJ45 1-1 split
- RJ45 1-4 split
- Bag with 6 screws and plug
- Sign Sensor
- Sign Horn/strobe
- Installation manual Mk9
- Quick-guide Mk9

APPROVALS

CE, EN55022 :2006/A1 :2007, EN55024/A2 :2003, EN61000-3-2 : 2006, EN61000-3-3/A2 :2006, AS/NZS CISPR 22 :2006, IEC/EN :IT55022/55024, LNE Règle de certification NF 128 rev 12 Nov 2007 (§2.1.2.4.3.) for the S8 CO2 Sensor Module. UL Certified. DIN6653-2:2015-06.

In the United States, the Mk9 system is in compliance with International Fire Code (IFC) 2015 Edition Section 5307.5.2.2, CGA G-6.5 2013, NFPA 55 2013 Edition 13.2.2 and NBIC Part 1 Supplement 3 S 3.4.

In compliance with EU Commission Directive 2006/15/EC of 7 Feb 2006 as well as OSHA – PEL (Permissible Exposure Limit) of TWA for CO2.