



The **CED 9000 (Delta III)** is designed using the highest quality materials and state-of-the-art technology providing our customers with consistent drink quality.

Features

- Stainless steel cabinet, water bath, product lines; removable refrigeration deck.
- available with 5 or 6 post-mix dispensing valves.
- all valves can be serviced independently.
- insulation is cfc-free, 0 gwp (global warming potential) structural foam.
- multiple non-carbonated drinks available through adjustable valve back block technology on 3 positions.
- consistent cold carbonation for improved drink quality.
- syrup and water are accessible from the rear of cabinet.
- compressor start delay protection.
- full wrap around merchandising.
- shrouded cabinet with illuminated graphics available.
- fully louvered top provides air circulation for more efficient operation.
- interchangeable refrigeration deck. possible options: r134a, r744, r290.

Certified by these agencies:



CUSTOMER SERVICE

Should you require more information about our products, please do not hesitate to contact our customer service team at lancerservice@lancerworldwide.com



WARRANTY

For warranty specifics by product, contact your Lancer Sales Representative. Equipment design and/or specifications are subject to change without notice.

For more Information visit lancerbeverage.com or call +61 8 8268 1388

Specifications

DIMENSIONS

Width: 429 mm / 16.88 inches
Depth: 649 mm / 25.78 inches
Height: 657 mm / 27.86 inches

ELECTRICAL REQUIREMENTS:

230VAC/50Hz, 4.5AMPs
230VAC/60Hz, 4.5AMPs
115VAC/60Hz, 9AMPs

WEIGHT:

Empty: 66.2 kg
Operating: 108 kg
Shipping: 73 kg

ICE:

Capacity: 11,3 - 12,7 kg

FITTINGS:

Water inlets: 9.5 mm / 3/8" male barb
Syrup inlets: 9.5 mm / 3/8" male barb

VALVES:

LEV® other valves available upon request

FLEX MANIFOLD CONFIGURATION:

5 Valve: 3-2 — 6 Valve: 3-3

KEY LOCK SWITCH

COMPRESSOR:

1/3 hp

MOTORS:

Agitator: 25 w
Condenser fan: 9 w

ICE BANK CONTROL:

Lancer Electronic Ice Bank Control

TRANSFORMER:

24VAC secondary

WATER:

capacity: 42 l