



FBD Partnership, LP | +852.2369.3998 | sales@fbdfrozen.com | fbdfrozen.com

563 50HZ SPECIFICATIONS

DIMENSIONS

Countertop unit: Width: 516 mm (20.3 in)

Depth: 820 mm (32.3 in)

Height: 1,052 mm (41.4 in) (with merchandiser door)

CAPACITY:

Barrel size: 5,205 ml

Continuous draw: 88,721 ml/hour Recovery time: 4 minutes

ELECTRICAL REQUIREMENTS:

230 VAC, 50 Hz, single phase, 3 wire, 20 Amp

REFRIGERATION:

14,300 BTU/Hr, R-404A (50Hz)

SPACE REQUIREMENT:

Sides and back: 51mm (2 in) minimum

Top: 305 mm (12 in) minimum

WEIGHT:

Operating unit: 177kg (390lb)

SYRUP CONNECTION

Bag-In-Box

MOTORS

Beater: (3) 120 W (1/6 HP) Fan: (1) 135 W (1/5 HP)


WATER REQUIREMENTS

Fresh water, minimum 10mm (3/8 in) supply, 207 kPa (30 psi) flowing

OPTIONAL ACCESSORIES

Base cart (Part #12-22493-0001) Leg kit (set of four) (Part #12-2533-0001) Painted or stainless steel side panels Water-cooled unit Merchandiser options (see spec sheet) Remote condenser (see spec sheet) Bib Rack

Install Kit









PRODUCT FEATURES



- Inline Carbonation[™] creates a more consistent over-run, quality and yield
- AccuFreeze[™] maintains product consistency, delivering the most consistent frozen beverage, drink after drink
- RapidFreeze[™] cold chamber system improves recovery and draw-time, while reducing the compressor workload, and increasing dispenser durability
- Electronic Simplicity offers easy-to-use keypad interface
- Optimal Use of Counter Space with minimum ventilation of two inches side or back
- Scroll[™] Compressor provides more reliable operation, and fewer moving parts than reciprocating compressors
- Customizable individual barrels allows for hundreds of different drink profile combinations, including sugar free options

