

6690-C

## FROZEN BEVERAGE FREEZER

Single flavor, Countertop, Gravity feed









### Powerful & Versatile

High capacity single flavor counter model for frozen beverage and milkshakes

#### **Fast Freeze Down**

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

#### Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

#### **Low Mix Indicator**

Light turns "ON" at low mix to alert operator to add mix

#### See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

#### **Standby & Indicator**

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator lights up during Standby

Higher capacity solution with greater flexibility to serve larger crowds mocktails frozen drinks including milkshakes

#### **Hopper Agitator**

Maintain product consistency and prevent product separation

#### **Self-closing Dispensing Valve**

Automatically prevents product overflow after dispense

#### **Safety Protections**

- $\boldsymbol{\cdot}$  High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating

#### **Light Box (Optional)**

- · Illuminates advertizing cards to attract more business
- Changes color to indicate Low Mix and Standby

#### **One-hand Operated Spinner (Optional)**


- · Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time






# 6690-C

## FROZEN BEVERAGE FREEZER





#### **SPECIFICATIONS**

Flavors	1
Freezing Cylinders	1 x 6.9L / 7.3qt
Mix Hoppers	1 x 20L / 21.2qt
Output Capacity (250ml)	240 serves/hr
Clearance Requirements	152mm/6″ on right

Weight	Kg/lb	
Net	138 / 304	
ShippingCylinders	151 / 333	
Volume	0.44 CBM / 15.48 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	454 / 17.9	520 / 20.5
Depth	657 / 25.9	860 / 33.9
Height	862 / 33.9	980 / 38.6

Electrical	Fuse	Amps	Power(kW)
220-240/50/1	20	12	2.4
208-230/60/1	20	13	2.6

#### **FEATURES**

Control System	Two, Mechanical
Refrigerated Hopper	lacksquare
Hopper Agitator	lacksquare
Standby Mode	lacksquare
Auto Closing Dispensing Valve	lacksquare
Low Mix Indicator Light	
Low Mix Indicator Alarm	$\checkmark$
Standby Indicator Light	lacksquare
High Pressure Protection	lacksquare
Thermal Overload Protection	ightharpoons

AVAILABLE OPTIONS	lacksquare
Top Air Discharge Chute	
Spinner	
Light Box	

· Above specifications are subject to change without notice